



Specifications:

Tech Specifications

- Panoramic-4k: 3840 x 1088; 4.15 MP YUV 4:2:2, MJPEG
- HD: 1920 x 1088; 2.1 MP YUV 4:2:2, MJPEG
- ~180° (H) x 54° (V)
- 188° DFOV
- Adjustable FOV through UVC PTZ command set
- Frame rate up to 30fps
- Latency: <= 5ms
- 5V Power Jack
- 0.3m to Infinity – Fixed Focus (each imager)
- 10 Lux
- Motion JPEG Built-in
- Auto 50/60 Hz Detect Built-In
- Color Controls
 - Sharpness
 - Brightness
 - Gamma
 - Saturation Control
 - White Balance (Man.)
- Status Indicator
 - LEDs Built-in
 - Lightweight ePTZ App (optional)
- Product Certifications
 - FCC Part 15 Class A (for commercial use only)
 - ROHS, REACH Compliant

System Requirements

- Plug-and-Play for Windows and Mac applications
- Supports USB Video Class (UVC) Driver
- USB 2.0/3.0
- Windows 7,8,8.1 or later
- Mac OS X 10.9 or later

Product Information

- Weight: 125g
- Width: 60 mm
- Height: 25 mm
- Length: 74 mm
- Operating Temperature: 0° C - 40° C
- Operating Humidity: 15%-85% (Non-Condensing)

What's In The Box?

- PanaCast® 2 Camera
- Table Stand/Wall Mount
- Quick Reference Guide
- USB 3.0 cable
- Power Adapter

Warranty

- You can find a detailed description of our [Warranty](#).

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

About Altia Systems



Altia Systems, Inc.
10020 N. De Anza Blvd, Suite 200
Cupertino, CA 95015
1-408-996-9710
www.getpanacast.com



Altia Systems® (altiasystems.com) is a venture-backed company based in Cupertino, CA, and is the creator of the PanaCast® Experience solution. The award-winning PanaCast® offers a unique experience that enables anyone on desktop or mobile to communicate in interactive, real-time Panoramic-HD 200° field-of-view video that replicates the human panoramic perspective.